

HDS 4.0/20-4 M Ea

HDS 3.5/23-4 M - the most powerful 3-phase hot water high-pressure cleaner in the Kärcher middle class. With 4-pole, water-cooled electric motor (220 V), 2 cleaning agent tanks and service electronics.

















1 Efficiency

- In the ecolefficiency mode the machine operates in the most economical temperature range (60°C) with full water flow.
- The burner cycles are optimised to reduce fuel consumption by 20% compared to full-load operation.

2 Maximum efficiency

- Proven and highly efficient burner technology.
- Four-pole electric motor with three-piston axial pump.

3 Operational safety

- The large, integrated water fine filter reliably protects the high-pressure pump against small dirt particles.
- The integrated exhaust gas thermostat switches off the drive motor if the emission temperature exceeds 300 °C.

4 Storage

- Safe and ample storage for protective gear, accessories and cleaning agents
- Storage hooks for power cable and high-pressure hose.





HDS 4.0/20-4 M Ea

- Economical eco!efficiency mode

Technical data

■ Included in the scope of supply.

2 cleaning agent tanks
 Three-phase motor: water-cooled

| Order no. | | 1.071 307.0 | | |
|--|-------------|---------------------|--------------------------------------|---|
| EAN code | | 886622014102 | | |
| Supply voltage | Ph / V / Hz | 1 / 220 / 60 | | |
| Flow rate | l/h | 450 - 910 | | |
| Pressure | bar / MPa | 30 - 138 / 3 - 13.8 | | |
| Pressure | PSI | 450 / 2000 | | |
| Temperature (for supply 12 °C) | °C | 80 / 155 | | |
| Connection load | kW | 6 | | |
| Consumption of heating oil or gas at full load | kg/h | 6 | | |
| Consumption of heating oil in eco!effi- ciency mode | kg/h | 4.8 | | |
| Fuel tank | 1 | 25 | | |
| Number of simultaneous users | | 1 | | |
| Portability | | cart | | |
| Weight | kg | 185 | | |
| Dimensions (L x W x H) | mm | 1330 × 750 × 1060 | | |
| Equipment | | | | |
| Cleaning agent function | | 20 + 10 tank | Service electronics with LED display | 1 |
| Spray gun | | EASY!Force Advanced | 2 cleaning agent tanks | |
| High-pressure hose | m | 15 / Longlife | Dry-running protection | |
| Spray lance | mm | 1050 | | |
| Power nozzle | | • | | |
| Servo control | | - | | |
| ANTI!Twist | | | | |
| Anti-twist system | | - | | |
| Tanks for cleaning agents, calcification protection and fuel that can be filled from the outside | | • | | |
| Control panel with display light | | | | |
| | | | | |

















| | | Order no. | Flow rate | | Price | Description |
|---|---|-------------|----------------|--|-------|--|
| Spray guns | | ' | | | | |
| EASY!Force Advanced | 1 | 4.118-005.0 | | | | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. |
| EASY!Force conversion kit 1 - from high-pressure hose | 2 | 4.111-050.0 | | | | For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle. |
| EASY!Force conversion kit 2 - from machine | 3 | 4.111-051.0 | | | | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters. |
| EASY!Force conversion kit 3 - high-pressure gun | 4 | 4.111-052.0 | | | | Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner. |
| Servo control | | | | | | |
| Servo Control | 5 | 4.118-008.0 | 750 - 1100 l/h | | | Water quantity and pressure regulated directly from the hand spray gun. |
| Quick connect | | | | | | |
| Quick coupling | 6 | 2.115-000.0 | | | | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray Lance interface. With M 22 x 1.5 internal thread. |
| Male coupling | 7 | 2.115-001.0 | | | | Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread. |

[■] Included in the scope of supply.

Available accessories.































| | | Order no. | Max. working pressure | Length | Price | Description | |
|--|------|-------------|-----------------------|------------|-------|--|-----|
| Rotating spray lances | | | | | | | t |
| Spray lance | 1 | 4.112-000.0 | 300 bar | 1050 mm | | 1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure. | |
| LED nozzle light | 2 | 2.680-002.0 | | | | Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours. | - 1 |
| Spray lance | 3 | 4.112-027.0 | 300 bar | 250 mm | | Spray lance, 250 mm, rotatable, ergonomic | |
| | 4 | 4.112-024.0 | 300 bar | 400 mm | | Spray lance, 400 mm, rotatable, ergonomic | |
| | 5 | 4.112-007.0 | 300 bar | 600 mm | | 600 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure. | ° [|
| | 6 | 4.112-006.0 | 300 bar | 840 mm | | 850 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure. | |
| | 7 | 4.112-018.0 | 300 bar | 1550 mm | | 1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure. | ° [|
| | 8 | 4.112-021.0 | 300 bar | 2050 mm | | 2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360' under pressure. | |
| Spray lance extender | 9 | 4.112-048.0 | 300 bar | 1000 mm | | Spray lance extension with EASY!Lock connection. Length 1000 mm. | |
| Double lance | 1 10 | 2.112-016.0 | 310 bar | 960 mm | 1 | OCO mm double lease for veriable pressure adjustment an | T |
| Double lance | 10 | 2.112-016.0 | 310 Ddi | 960 111111 | | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). | |
| Angular spray lance Spray lance for toilets and rain gutters | 11 | 4.112-029.0 | | | | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | |
| Flexible spray lance | | | | | | | |
| Flexible lance | 12 | 4.112-035.0 | 210 bar | 1050 mm | | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | |
| High pressure articulated joint | 13 | 4.112-057.0 | 300 bar | | | For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer. | |
| Gutter cleaner | 1 | | 1 | | 1 | | |
| Gutter cleaning lance | 14 | 2.112-015.0 | | 960 mm | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | |
| Undercarriage spray lance | | | 1 | | _ | | |
| Underbody lance | 15 | 4.112-032.0 | | 700 mm | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | |
| Additional handle Additional handle for EASY!Lock spray lances | 16 | 4.321-380.0 | cessories. | | | Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjus your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility. | |





| | | Order no. | Nozzle size | | Price | Description |
|------------------------------|---|-------------|-------------|--|-------|---|
| Power nozzle spray angle 25° | | | | | | |
| Power nozzle | 1 | 2.113-026.0 | 60 | | | Fan jet nozzle for large-area coverage and stubborn dirt and stains. |
| HP nozzle spray angle 0° | | | | | | |
| Power nozzle | 2 | 2.113-036.0 | 60 | | | Solid jet for very stubborn dirt and stains. |
| Power nozzle spray angle 15° | | | | | | |
| Power nozzle | 3 | 2.113-048.0 | 60 | | | Fan jet nozzle for stubborn dirt and stains. |
| Power nozzle spray angle 40° | | | | | | |
| Power nozzle | 4 | 2.113-056.0 | 75 | | | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. |

lacksquare Included in the scope of supply. \Box Available accessories.

















| | | Order no. | ID | Max. working pressure | Length | Price | Description | |
|-----------------------------------|-------|-------------|-------|-----------------------|--------|-------|--|---|
| Longlife 400 with unions on both | sides | | | | | | | |
| High-pressure hose Longlife | 1 | 6.110-038.0 | DN 8 | 400 bar | 10 m | | Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both sides and ANT!!Twist. Approved for 400 bar pressure. | • |
| | 2 | 6.110-024.0 | DN 8 | 400 bar | 1.5 m | | 1.5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure. | |
| | 3 | 6.110-023.0 | DN 8 | 400 bar | 30 m | | Robust high-pressure hose with double steel core, AN- TI!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, for up to 400 bar pressure. | |
| | 4 | 6.110-027.0 | DN 8 | 400 bar | 20 m | | High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides. | |
| | 5 | 6.110-029.0 | DN 8 | 400 bar | 15 m | | The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar. | |
| Standard with unions on both side | !S | | | | | | | |
| High-pressure hose | 6 | 6.110-031.0 | DN 8 | 315 bar | 10 m | | High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANT!!Twist and 10 m long. | |
| | 7 | 6.110-030.0 | DN 8 | 315 bar | 15 m | | 15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides. | |
| | 8 | 6.110-032.0 | DN 8 | 315 bar | 20 m | | 20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar. | |
| | 9 | 6.110-014.0 | DN 8 | 315 bar | 30 m | | Comfortable length (30 m) and innovative EASY!Lock manual screw fitting: High-pressure hose (DN 8) with ANT!!Twist for pressures up to 315 bar. | |
| | 10 | 6.110-042.0 | DN 10 | 220 bar | 15 m | | Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10). | |
| | 11 | 6.110-043.0 | DN 10 | 220 bar | 20 m | | 20 m in length and the extremely time-saving and comforta- ble EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10). | |
| | 12 | 6.110-044.0 | DN 10 | 220 bar | 25 m | | Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar. | |
| | 13 | 6.110-045.0 | DN 10 | 220 bar | 40 m | | 40 m long high-pressure hose with EASYILock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar. | |
| | 14 | 6.110-059.0 | DN 12 | 210 bar | 15 m | | Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides. | |
| | 15 | 6.110-060.0 | DN 12 | 210 bar | 40 m | | With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar. | |
| | 16 | 6.110-041.0 | DN 10 | 220 bar | 10 m | | Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar. | |











| | | Order no. | ID | Max. working pressure | Length | Price | Description | |
|---|----------|------------------|------|-----------------------|--------|-------|---|--|
| Food industry version with unions | on bot | th sides | | | | | | |
| High-pressure hose food grade | 17 | 6.110-051.0 | DN 8 | 250 bar | 10 m | | High-pressure hose (ID 6), 10 m long, with grey, non-marking outer covering. Approved for use in the food industry. With quick and robust EASY!Lock hand screw connection at both ends. | |
| | 18 | 6.110-052.0 | DN 8 | 250 bar | 20 m | | Suitable for use in food industry: 20 m long high-pressure hose (ID 8) with grey, non-marking outer covering, AN-TI!Twist and EASY!Lock hand screw connections. | |
| Longlife food design with screw co | onnectio | ons at both ends | | | | | | |
| High-pressure hose food grade Longlife | 19 | 6.110-053.0 | DN 8 | 400 bar | 10 m | | With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, AN-TI!Twist and EASY!Lock hand screw connection at both ends. | |
| Special hoses | | | | | | | | |
| High-pressure hose curved | 20 | 6.110-068.0 | DN 8 | 400 bar | 1.5 m | | For connection to hose reels: high-pressure hose, with M 22 × 1.5 connection and curved EASY!Lock hand screw connection. 1.5 m long, suitable for up to 400 bar working pressure. | |

[■] Included in the scope of supply.

Available accessories.











| | | Order no. | | | Price | Description | |
|--------------|---|-------------|--|--|-------|--|--|
| Weed control | | | | | | | |
| WR 50 | 1 | 2.114-013.0 | | | | In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter. | |
| WR 20 | 2 | 2.114-014.0 | | | | For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter. | |
| WR 100 | 3 | 2.114-015.0 | | | | Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners. | |
| WR 10 | 4 | 2.114-016.0 | | | | In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter. | |

[■] Included in the scope of supply.

□ Available accessories.







| | | Order no. | Max. working pressure | Nozzle size | | Price | Description | |
|---------------------------|---|-------------|-----------------------|-------------|--|-------|---|--|
| Dirt blaster, large | | 1 | ı | | | | | |
| Dirt blaster | 1 | 4.114-036.0 | 300 bar | 55 | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | |
| Angled vario nozzle 0-90° | | | | | | | | |
| Angled Vario nozzle | 2 | 4.113-008.0 | | 55 | | | Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces. | |

[■] Included in the scope of supply.

Available accessories.































| | | | 1 | | | | I | |
|---|--------|----------------------------|---|---|----|-----|---|-----|
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | Order no. | | | Pr | ice | Description | |
| Nozzle union | | | | | | | | |
| Nozzle screws | 1 | 4.112-011.0 | | | | | Nozzle screws with protectors for high-pressure and power nozzles | r 🗆 |
| Cleaning agent injector | | | | | | | | |
| Cleaning agent injector for high and low pressure (without nozzles) | 2 | 4.637-032.0 | | | | | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%. | |
| Cleaning agent injector for high pressure (without nozzle) | 3 | 4.637-033.0 | | | | | Cleaning agent dosage at high pressure 3 - 5 % | |
| Machine-specific nozzle kit with ord | der no | . 4.637-033.0 | | | | | | |
| Nozzle kit 1000-1200 l/h | 4 | 4.769-013.0 | | | | | For HD/HDS 1000 - 1200 l/h. Consists of nozzle insert + HI power nozzle + union | , _ |
| Nozzle insert with order no. 4.637- | 032.0 | | | | | | | |
| Nozzle insert up to 1,100 l/h - high pressure | 5 | 4.769-003.0 | | | | | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h. | |
| Nozzle insert up to 1,100 l/h - low pressure | 6 | 4.769-001.0 | | | | | For low pressure with machines up to 1.100 l/h | |
| Rotary coupling | | | | ' | | | | |
| Rotary coupling | 7 | 4.111-021.0 | | | | | Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection | |
| Connector | | | | | | | | |
| Screw socket for surface cleaners and Servo Control controllers | 8 | 4.111-022.0 | | | | | For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) - $1 \times M 22 \times 1.5/1 M 18 \times 1.5$. | - 1 |
| Y distributor | 9 | 4.111-024.0 | | | | | Offers the option to connect two spray units to the machin- Installation on the high pressure outlet. | e |
| Short spray unit | 10 | 4.111-038.0 | | | | | For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles. | |
| EASY!Lock adapter | | | | | | | | |
| Adapter 1 M22AG-TR22AG | 11 | 4.111-029.0 | | | | | Adapter 1 to connect the old hose with the new hose | |
| Adapter 2 M22IG-TR22AG | 12 | 4.111-030.0 | | | | | Adapter 2 to connect the old device with the new hose and the old gun with the new hose | |
| Adapter 3 M22IG-TR22AG | 13 | | | | | | Adapter 3 to connect the old gun with the new spray lance and new servo regulator | |
| Adapter 4 TR22IG-D11 | 14 | | | | | | Adapter 4 to connect the new gun with the old swivel hose | - |
| Adapter 5 TR22IG-M22AG | 15 | 4.111-033.0 | | | | | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance | |
| Adapter 6 TR22IG-M22AG | 16 | 4.111-034.0 | | | | | Adapter 6 to connect the new device with the old hose and the old hose with the new gun | |
| Adapter 7 M18IG-TR20AG | 17 | 4.111-035.0 | | | | | Adapter 7 to connect the old spray lance with the new nozzle | |
| Adapter 8 TR20IG-M18AG | 18 | 4.111-036.0 | | | | | Adapter 8 to connect the new spray lance with the old nozzle | |
| Adapter hose extension 9 TR | 19 | 4.111-037.0 | | | | | Adapter 9 to connect the new hose with the new hose | |
| Adapter 12 rotary coupling EASY!Lock 22 IG - M22 x 1.8 AG | 20 | 4.111-046.0 | | | | | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection | , [|
| Flue pipe | | | | | | | | |
| Flue gas adapter | 21 | 4.656-149.0 4.656-080.0 | | | | | Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system). | |
| | | I . | 1 | | | | j byblenn. | - 1 |



























| | | Order no. | Max. working pressure | Nozzle size | Diame- ter | Price | Description | |
|---|--------|------------------|-----------------------|-------------|---------------|-------|--|-----|
| Pipe cleaning hose, ID 6 | | | | | | | | Ţ |
| Pipe cleaning hose, ID 6, 10 m, max. 250 bar | 1 | 6.110-046.0 | 250 bar | | | | The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection fo nozzle R 1/8). | r [|
| Pipe cleaning hose, ID 6, 20 m, max. 250 bar | 2 | 6.110-008.0 | 250 bar | | | | The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection fo nozzle R 1/8). | r [|
| Pipe cleaning hose, ID 6, 30 m, max. 250 bar | 3 | 6.110-047.0 | 250 bar | | | | The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection fo nozzle R 1/8). | r [|
| Pipe cleaning nozzle | | | | | | | | |
| Pipe cleaning dirt blaster D21/060 | 4 | 4.765-002.0 | | 60 | 21 mm | | The forward-tilted rotating pencil jet removes the most | Ε |
| Pipe cleaning dirt blaster D30/060 | 5 | 4.765-005.0 | | 60 | 30 mm | | stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling. | |
| Pipe cleaning nozzle 120 | 6 | 5.763-089.0 | | 120 | 24 mm | | Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle. | |
| Pipe cleaning nozzle | 7 | 5.763-019.0 | | 65 | 16 mm | | 16 mm pipe cleaning nozzle with internal thread. Various je | _ |
| | 8 | 5.763-016.0 | | 60 | 16 mm | | directions for environmentally-friendly cleaning of blocked drains and pipes. | |
| | 9 | 5.763-021.0 | | 70 | 30 mm | | 30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes. | |
| Rotating pipe cleaning nozzle | 10 | 6.415-440.0 | | 65 | 16 mm | | Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes. | |
| Drum and tank cleaning | | | | | | | blocked drains and pipes. | |
| Add-on kit mud sucker | 11 | 2.641-798.0 | | | | | For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps. | |
| Barrel and tank cleaning | | | 1 | | | | | |
| Barrel cleaner BC 14/12 | 12 | 2.112-020.0 | | | | | The BC 14/12 barrel cleaner is a spray unit for the interior cleaning of containers and barrels – especially oak barrels with a capacity of between 225 and 600 litres. | |
| HKF 50 spray head, brass | | | , | | | | | |
| HKF 50 M spray head | 13 | 3.631-039.0 | | | | | Constant rotational speed and lightweight design: The compact interior cleaning head for cleaning vats and tanks with openings of 50 mm or wider. | |
| | 14 | 3.631-058.0 | | | | | Compact interior cleaning head for cleaning containers with openings of 50 millimetres or wider. The device stands out from the crowd with its constant rotational speed and lightweight design. | l |
| Nozzle kit for spray head HKF 50 (3 | .631-0 | 009.0 / 3.631-03 | 9.0) | | | | | |
| Nozzle 045 for 2-nozzle operation HKF 50 | 15 | 6.415-446.0 | | 45 | | | Nozzle for dual-nozzle operation | |
| Nozzle 090 for 1-nozzle operation HKF 50 | 16 | 6.415-447.0 | | 90 | | | Nozzle for single-nozzle operation | |
| Double grip for precise control of spray head | 17 | 2.863-036.0 | | | | | Double handle. Precise control of the spray head | |
| Screw plug for using a spray head with one nozzle | 18 | 5.411-061.0 | | | | | Screw plug for using a spray head with one nozzle | Г |

lacksquare Included in the scope of supply. \Box Available accessories.





















| | | Order no. | Flow rate | Nozzle size | Diame- ter | | Price | Description | |
|--|----|-------------|----------------|-------------|---------------|--|-------|--|---|
| Hard Surface Cleaner FRV 30 | | | | II. | | | | ' | |
| Hose fastening attachment kit | 1 | 2.642-528.0 | | | | | | Suction cup for fixing the suction hose to smooth surfaces. | |
| Dirt trap attachment kit | 2 | 2.642-532.0 | | | | | | Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas. | |
| FR 30 Me surface cleaner | | | | , | | | | | |
| Hard Surface Cleaner FR 30 Me | 3 | 2.111-013.0 | | | 300 mm | | | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | |
| Hard Surface Cleaner FR 50 | | | | | | | | | |
| Surface Cleaner FR 50 Me | 4 | 2.111-023.0 | | | 500 mm | | | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceram ic bearings, push handle, non-marking swivel castors and detergent dosing system. | |
| Machine-specific nozzle kits for FF | 1 | | | | | | | | |
| Nozzle kit for FR | | 2.640-442.0 | 850 - 1100 l/h | | | | | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h). | |
| Machine-specific nozzle kits for FF | RΛ | | | | | | | | , |
| Nozzle kit for FRV | 6 | 2.642-982.0 | | 80 | | | | Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30. | |
| FRV 30 Me surface cleaner | | | | | | | | | , |
| Extension hose FRV 30 Me and FRV 50 Me | 7 | 4.441-040.0 | | | | | | 5 m extension hose for FRV 30 Me. Includes connecting adapter. | |
| FRV 30 Me Surface Cleaner | 8 | 2.111-012.0 | | | | | | Thanks to automatic suction of the dirty water, the stainles: steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. | |
| Surface Cleaner FR 50 Me | | | • | | | | | | |
| FRV 50 Me surface cleaner | 9 | 2.111-024.0 | | | | | | Surface cleaning with automatic suction of the dirty water for very large surfaces - this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C | |

[■] Included in the scope of supply.

Available accessories.



























| | | Order no. | Flow rate | | Price | Description |
|---|----|-------------|--------------------|---|-------|---|
| Cup foam lance | | | | | | |
| Cup foam lance Basic 3 | 1 | 4.112-055.0 | 900 - 2500 l/h | | | High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality. |
| 1-litre cleaning agent container for cup foam lance basic | 2 | 5.071-414.0 | | | | For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0). |
| Cup foam lance Advanced | 3 | 2.112-018.0 | | | | Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design. |
| 1-litre cleaning agent container for cup foam lance advanced | 4 | 6.414-050.0 | | | | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0). |
| Cup foam lance Advanced 3 | 5 | 4.112-065.0 | 900 - 2500 l/h | | | Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher. |
| Cup foam lance DUO Advanced 3 | 6 | 4.112-069.0 | 900 - 2500 l/h | | | DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank. |
| Inno Foam Kit | | , | | , | ' | |
| Inno Foam Set with detergent injector | 7 | 2.112-000.0 | | | | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and |
| Inno Foam Set | 8 | 2.112-008.0 | | | | stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. |
| Easy Foam Set | | | | | | |
| Easy Foam Set with RM injector | 9 | 2.112-010.0 | | | | HP foam system for use with. HD/HDS units for cleaning and \Box |
| Easy Foam Set | 10 | 2.112-011.0 | | | | disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. |
| Nozzle kits for Inno/Easy Foam Set | | | | | | |
| Nozzle kit 110 for Inno / Easy Set 1,000-1,300 l/h | 11 | 2.111-020.0 | 1000 - 1300 l/h | | | Nozzle kit 110 contains Kärcher power nozzles and nozzle inserts. For Inn/Easy-Foam set 1000-1300 l/h. For optimal foam system performance. |
| Foam nozzle mounting kit | | | | | | |
| Foam nozzle attachment kit | 12 | 2.112-013.0 | | | | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. |

 $[\]blacksquare$ Included in the scope of supply. $\hfill\Box$ Available accessories.





















| | | Order no. | Length | | Price | Description | |
|--|--------|-------------|--------|--|--------|---|------|
| Automatic, self-winding hose reels | for wa | | | | 111100 | | _ |
| Automatic plastic hose reel incl. high-pressure hose | 1 | 2.639-257.0 | 15 m | | | Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety. | |
| Automatic hose reel, powder-coated steel / plastic | 2 | 6.392-074.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. | |
| Automatic stainless steel / synthetic material hose drum | 3 | 6.392-083.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. | |
| Automatic hose reel, coated | 4 | 6.392-106.0 | 20 m | | | Automatic hose reel of durable plastic. Painted steel bracket Suitable for 20 m high-pressure hose. | : |
| Hose reel, automatic, basalt grey-coated | 5 | 6.392-105.0 | 20 m | | | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife). | П |
| Automatic hose reel, stainless steel, includes swivel holder | 6 | 6.392-076.0 | 20 m | | | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | |
| Automatic stainless steel hose reel | 7 | 6.392-442.0 | 40 m | | | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit). | - _ |
| Powder-coated swivel holder | 8 | 2.639-931.0 | | | | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel. | è. 🗆 |
| Stainless steel swivel holder | 9 | 2.641-867.0 | | | | Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose. | - |
| Automatic, self-winding hose reel a | ttachr | nent kit | | | | | |
| Attachment kit automatic hose reel HDS M/S | 10 | 2.110-011.0 | | | | Automatic hose reel as a complete attachment kit that's easy to mount. Suitable for HDS medium and super class. For maximum convenience when winding and unwinding the high-pressure hose. | y |
| Attachment kit automatic hose reel holder HDS M/S | 11 | 2.110-020.0 | | | | Holder includes connection material for installing an automatic hose reel to machines in the HDS Middle and Super classes. | |

[■] Included in the scope of supply.

Available accessories.



| | | Order no. | Flow rate | Length of the product | Length | Price | De- scrip- tion | | |
|-------------------|--|-----------|-----------|-----------------------|--------|-------|-----------------------|--|--|
| Telescopic lances | | | | | | | | | |

[■] Included in the scope of supply.

□ Available accessories.















| | | | | | | | De- | |
|-------------------|---|-------------|-----------|-----------------------|--------|-------|----------------|--|
| | | Order no. | Flow rate | Length of the product | Length | Price | scrip- tion | |
| Hoses | | | | | | | | |
| iSolar HP hose 7 | 1 | 6.392-978.0 | | | 8.5 m | | | |
| iSolar HP hose 10 | 2 | 6.392-977.0 | | | 11.5 m | | | |
| iSolar HP hose 14 | 3 | 6.392-976.0 | | | 15 m | | | |

[■] Included in the scope of supply.

Available accessories.









| | | Order no. | Nozzle size | | Price | Description | |
|---|--------|-------------|-------------|--|-------|---|--|
| Wet blasting attachment (without n | ozzle) | | | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.115-000.0 | | | | Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet. | |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.115-006.0 | | | | Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet. Without flow control. | |
| Nozzle kits for wet jet unit | | | | | | | |
| Nozzle kit for wet jet unit 065 | 3 | 2.112-026.0 | 65 | | | Consisting of wet jet nozzle and nozzle insert - only for use in combination with wet jet unit 4.115-000.0 4.115-006.0. | |
| Boron carbide nozzle | | | | | | | |
| Boron carbide nozzle, for machines up to 1,000 l/h | 4 | 6.415-084.0 | 6 mm | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. | |

[■] Included in the scope of supply.

Available accessories.













| | | 1 | 1 | | | |
|--|---|-------------|---|--|-------|--|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | Order no. | | | Price | Description |
| Attachment kit for transport | | | ' | | | |
| Transport eyelet attachment kit | 1 | 2.644-053.0 | | | | Robust transport eyelet attachment kit for the secure fixing of HDS Medium and Super Class pressure washers during transport. |
| Flame monitoring attachment kit | | | | | | |
| Flame monitoring attachment kit for HDS Middle and Super Class | 2 | 2.641-796.0 | | | | More safety thanks to ABS HDS M/S flame monitoring system: A light sensor monitors the burner flame. The fuel supply cuts out automatically if the flame extinguishes. |
| Accumulator kits | | | | | | |
| Pressure tank attachment kit for HDS Middle and Super Class | 3 | 2.641-803.0 | | | | The accumulator can be mounted on the HDS machine in order to dampen pressure surges, which conserves the machine's line system. |
| Remote control set | | | | | | |
| Remote control attachment kit for HDS Middle and Super Class | 4 | 2.642-157.0 | | | | Remote control for the machines of the HDS Middle and Super class with the functions on/off, hot/cold water and cleaning agent on/off. For mounting to a wall. |
| Coin-op remote control | | | | | | |
| Coin remote control attachment kit for HDS Middle and Super Class | 5 | 2.642-158.0 | | | | Retrofittable coin acceptor for machines in the HDS Middle and Super class for self-service operation. For installation on the machine. |

[■] Included in the scope of supply.

□ Available accessories.





















| | | | | | | | _ |
|--|----|----------------------------|--|---|-------|--|---|
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | Order no. | | | Price | Description | |
| Geka coupling | | 1 | | | | | |
| Geka connector with hose barb, R 3/4" | 1 | 6.388-455.0 | | | | with hose liner | |
| Geka connector with hose barb, R 1" | 2 | 6.388-465.0 | | | | with hose barb | |
| Geka connector with internal thread, R 1" | 3 | 6.388-458.0 | | | | with female thread | |
| Suction filter | | | | | | | |
| Water suction filter | 4 | 6.414-956.0 | | | | Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve | r |
| Suction filter with check valve | 5 | 4.730-012.0 | | | | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | |
| Water fine filter | | | | | | | |
| Universal water fine filter, 25 μm | 6 | 2.637-020.0 | | | | Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter. | |
| Water fine filter, with adapter | 7 | 4.730-102.0 | | | | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | _ |
| Water fine filter, 100 µm, R 1" | 8 | 2.638-270.0 | | | | Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1". | |
| Water supply hose | | | | | | | |
| Water supply hose | 9 | 4.440-207.0 4.440-270.0 | | | | NW 19 R1" / R 3/4", up to 85 °C, for pick-up NW 19 R1" / R1", up to 85 °C | |
| Backflow check valve | 10 | 4.440 270.0 | | | | 1 NW 13 K1 / K1 , Op to 65 C | |
| Backflow preventer | 11 | 2.641-374.0 | | | | To prevent detergent getting into the drinking water cycle i case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakag protection | l |
| Other HP Accessories | | | | • | | | |
| Jet gun | 12 | 2.869-067.0 | | | | Short set-up time, easy transport, instant switch off - the je gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume. | |

[■] Included in the scope of supply. □ Available accessories.









| | | Order no. | Flow rate | | Price | Description | |
|--|---|-------------|----------------|--|-------|--|--|
| Push-on washing brush | | | | | | | |
| Push-on wash brush | 1 | 4.113-001.0 | | | | For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18 x 1.5 $\hfill\Box$ | |
| Rotating washing brush | | | | | | | |
| Rotating wash brush for > 800 l/h machines, nylon bristles | 2 | 4.113-002.0 | 800 - 1300 l/h | | | Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to | |
| Rotating wash brush for > 800 l/h machines, natural bristles | 3 | 4.113-005.0 | 800 - 1300 l/h | | | 60°C, M 18 x 1.5 (replaceable brush insert). | |

[■] Included in the scope of supply.

□ Available accessories.