

SC6500™







The SC6500™ Rider Scrubber

Tough on dirt. Easy on operators.

Experience the combination of effortless control and efficient, sustainable scrubbing in one powerful, compact package: the Advance $SC6500^{TM}$ rider scrubber. The tight turning radius, simple operation and up to 48 inch cleaning path of the SC6500 makes cleaning the dirtiest floors a breeze for virtually anyone.







Efficient scrubbing.



With the tightest aisle turn in its class and large, 70 gallon solution and recovery tanks to maximize scrubbing time, the SC6500 helps you get the job done faster. And, with a high power scrub deck, a single pass is all you need to get an amazingly clean floor.

Rugged construction.



Don't let the smooth, precise acceleration of its maintenance-free AC brushless propulsion drive fool you. With an industrial bumper, frame-mounted deflectors and a tubular, steel construction all specifically engineered for the most severe industrial applications, the SC6500 is as tough as they come and built to last.

Versatile operation.



The SC6500 represents cleaning the way it *should* be—that is, exactly how you want it. With the optional EcoFlex™ system that allows you to use only the amount of chemical needed, an offset scrub deck that effectively cleans hard-to-reach edges and an ergonomic design compatible with your operators, the SC6500 easily adapts to the conditions you throw at it.

An Industrial Scrubbing Powerhouse









high productivity cleaning in a single pass.



Removable, high capacity detergent cartridge for sustained flexible cleaning is available with optional EcoFlex™ System.

Under the hood.

SC6500™ Specifications

Models	SC6500 [™] 40C	SC6500 [™] 45C	SC6500 [™] 48C	SC6500 [™] 40D	SC6500 [™] 45D	SC6500™ 48D
	Scrubbing and Recovery Systems					
Scrub Deck Type	Cylindrical			Disc		
Scrub Path	40 in (102 cm)	45 in (114 cm)	48 in (122 cm)	40 in (102 cm)	45 in (114 cm)	48 in (122 cm)
Scrubbing Coverage Rate Per Hour (Max.)	96,800	108,900	116,200	96,800	108,900	116,200
Scrub Brush Size	40 in x 8.5 in	45 in x 8.5 in	48 in x 8.5 in	2 x 20 in (51 cm)	3 x 16 in (41 cm)	3 x 17 in (43 cm)
	(102 cm x 22 cm)	(114 cm x 22 cm)	(122 cm x 22 cm)			
Scrub Brush Speed	630 rpm			240 rpm	225 rpm	225 rpm
Brush Motor Power	2 x 1.5 hp (1.13 kW)			1 x 3.0 hp (2.24 kW)	3 x 1.5 hp (1.13 kW)	3 x 1.5 hp (1.13 kW)
Sweeping Path	57 in (145 cm)			_		
Debris Hopper Capacity	0.40 ft ³ (11 L)	0.44 ft ³ (12.5 L)	0.50 ft ³ (14 L)		_	
Solution/Recovery Tank Capacity	70 gal (265 L)					
Vacuum Motor	0.8 hp (0.6 kW) - dual vac optional					
Waterlift	Single Vac - 64 in (163 cm) / Dual Vac - 67 in (170 cm)					
	Battery and Propulsion System					
Battery Options / Maximum Run Time*	36 V, 420 Ah C20 – Up to 3.0 hrs. – 40 Cyl / 3.5 hrs. – 40 Disc					
	36 V, 450 Ah C6 (monoblock) – Up to 3.75 hrs. – 40 Cyl / 4.75 hrs. – 40 Disc					
Propulsion System	Variable speed AC brushless drive					
Propel Speed Forward	6.0 mph (9.5 km/h)					
Propel Speed Reverse	3.0 mph (5 km/h)					
Propel Motor (Peak)	3.0 hp (2.25 kW)					
Gradeability Transport @ Gross Weight	16% (9°)					
Scrubbing	10.5% (6°)					
	Dimensions / Weight / Sound					
Length	74 in (187 cm)					
Width	48 in (121 cm)	54 in (136 cm)	56 in (141 cm)	43 in (108 cm)	52 in (131 cm)	53 in (133 cm)
Height	50 in (149 cm)					
Minimum Aisle Turn	84 in (214 cm)					
Weight GVW	3,325 lb (1,508 kg)	3,365 lb (1,508 kg)	3,410 lb (1,547 kg)	3,220 lb (1,460 kg)	3,270 lb (1,483 kg)	3,320 lb (1,506 kg)
Empty	2,897 lb (1,314 kg)	2,937 lb (1,332 kg)	2,982 lb (1,353 kg)	2,792 lb (1,266 kg)	2,842 lb (1,289 kg)	2,892 lb (1,312 kg)
Sound Level IEC 60335-2-72, ISO 11201*	70 dB A					

Specifications subject to change without notice.

*Run-time will vary based on machine configuration and operating conditions.





SC6500™

Optional Accessories:

- Tubular steel heavy duty bumper
- · Heavy duty front bumper
- Deluxe Grammer seat and seat belt kit
- Refillable detergent cartridge
- CoolTool scrub and vac wand kit
- Recovery tank drain hose extension
- · Floor mat kit
- 2nd vac motor kit

- Warning beacon kit
- · Front headlight kit
- · Back-up alarm kit
- · Seat belt kit for standard seat
- · Overhead guard
- · Operator foot guard kit
- Solution auto-fill kit
- Battery roll out kit for 450 Ah C6 battery (batteries not included)





SC6500™

14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com Phone 800-850-5559 Fax 800-989-6566

240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca Phone 800-668-8400 Fax 800-263-5111



TrackClean

Centralized Fleet Management

Increase productivity with TrackClean asset management technology installed on your fleet of machines to monitor, verify and improve operational effectiveness. Learn more: http://www.advance-us.com/TrackClean

Visit http://www.advance-us.com/SC6500 or contact your Advance sales representative to learn more.

©2015 Nilfisk-Advance, Inc. Form L3398A 1-12-15

