

Printing date 04/20/2017

Reviewed on 04/13/2017

1 Identification

- · Product identifier
- · Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS
- · Article number: 13-8750, 8750
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UCP PAINT INC. 19500 Rte Transcanadienne Baie D'Urfe,H9X 3S4, Quebec ,Canada (514) 457-1512

- · Information department: Product safety department
- · Emergency telephone number: Chemtrec: 24 Hours 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids - Category 3

H226 Flammable liquid and vapour.



GHS08 Health hazard

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn

Specific Target Organ Toxicity - Repeated Exposure - Category 1

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Aspiration Hazard - Category 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

(Contd. of page 1)

· Hazard-determining components of labeling:

Stoddard solvent

octamethylcyclotetrasiloxane

A mixture of: butan-2-one oxime and syn-O,O'-di(butan-2-one oxime)-diethoxysilane

· Hazard statements

Flammable liquid and vapour.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

Ground and bond container and receiving equipment.

Keep container tightly closed.

Use non-sparking tools.

Take actions to prevent static discharges.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Hazard description:
- · WHMIS-symbols:

B3 - Combustible liquid

D2A - Very toxic material causing other toxic effects



- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 2Reactivity = 0

(Contd. of page 2)

Safety Data Sheet according to HPR, Schedule 1

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

· HMIS-ratings (scale 0 - 4)

Fire = 2REACTIVITY 0

Health = *1

Reactivity = 0

3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
8052-41-3	Stoddard solvent	15-40% w/w
556-67-2	octamethylcyclotetrasiloxane	3-7% w/w
64742-47-8	Distillates (petroleum), hydrotreated light	3-7% w/w
96-29-7	A mixture of: butan-2-one oxime and syn-O,O'-di(butan-2-one oxime)-diethoxysilane	0,1-<1% w/w

4 First aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

8052-41-3 Stoddard solvent

EL Short-term value: 580 mg/m³ Long-term value: 290 mg/m³

64742-47-8 Distillates (petroleum), hydrotreated light

EL Long-term value: 200 mg/m³ Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

 Information on 	basic physical	l and chemica	properties
------------------------------------	----------------	---------------	------------

· General Information

· Appearance:

Form:

Liquid

Color:

Dark grey

· Odor:

Mild

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

161 °C

· Flash point:

41 °C

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

210 °C

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

(Contd. on page 6)

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

	(Contd. of page
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	1,1 Vol %
Upper:	6,0 Vol %
· Vapor pressure:	Not determined.
· Density at 20 °C:	1,32997 g/cm ³
· Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/w	ater): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0,5 %
Solids content:	21,6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

(Contd. on page 7)

K

Safety Data Sheet according to HPR, Schedule 1

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

 (Contd. of page 6)

 • Carcinogenic categories

 • IARC (International Agency for Research on Cancer)

 13463-67-7 titanium dioxide
 2B

 14808-60-7 Quartz (SiO2)
 1

 1333-86-4 Carbon black
 2B

 136-52-7 cobalt bis(2-ethylhexanoate)
 2B

 7631-86-9 silicon dioxide, chemically prepared
 3

 1330-20-7 xylene
 3

12 Ecological information

14808-60-7 Quartz (SiO2)

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:

· NTP (National Toxicology Program)

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, TDG, IMDG, IATA	UN1263	
· UN proper shipping name		
$\cdot DOT$	Paint	
· TDG	1263 Paint	
· IMDG, IATA	PAINT	

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

(Contd. of page 7) · Transport hazard class(es) $\cdot DOT$ · Class 3 Flammable liquids ·Label 3 · TDG, IMDG, IATA · Class 3 Flammable liquids ·Label 3 · Packing group III· DOT, TDG, IMDG, IATA Not applicable. · Environmental hazards: · Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 30 F-E,<u>S-E</u> · EMS Number: · Stowage Category A · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ On passenger aircraft/rail: 60 L · Quantity limitations On cargo aircraft only: 220 L $\cdot TDG$ · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

Section 313	(Specific toxic chemical listings):	(Contd. of pa
	methanol	·
	cobalt bis(2-ethylhexanoate)	
	2-(2-methoxyethoxy)ethanol	
	Phthalocyanine Blue	
	1,2,4-trimethylbenzene	
1330-20-7	•	111 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	ic Substances Control Act):	
·	Calcium Carbonate	
	octamethylcyclotetrasiloxane	
	Distillates (petroleum), hydrotreated light	
	titanium dioxide	
	LECITHIN	• .
3020 70 0	Lecithins,soya	
14808-60-7	Quartz (SiO2)	****
67-56-1	methanol	
20344-49-4	iron hydroxide oxide	
	Carbon black	
136-52-7	cobalt bis(2-ethylhexanoate)	
	Solvent naphtha (petroleum), medium aliph.	
	Hexanoic acid, 2-ethyl-	
	manganese salt	
111-77-3	2-(2-methoxyethoxy)ethanol	
7631-86-9	silicon dioxide, chemically prepared	
21645-51-2	aluminium hydroxide	
107-98-2	1-methoxy-2-propanol	
149-57-5	2-ethylhexanoic acid	
147-14-8	Phthalocyanine Blue	
79-09-4	propionic acid	
95-63-6	1,2,4-trimethylbenzene	·
1330-20-7	xylene	
108-67-8	mesitylene	
7732-18-5	water, distilled, conductivity or of similar purity	
Canadian s	ubstance listings:	
Canadian I	Domestic Substances List (DSL)	
8052-41-3	Stoddard solvent	
556-67-2	octamethylcyclotetrasiloxane	
	Distillates (petroleum), hydrotreated light	
	titanium dioxide	
8030-76-0	LECITHIN	
14900 60 7	Lecithins, soya	
	Quartz (SiO2)	
0/-30-1	methanol	(Contd. on pag

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

	(Contd. of pag
20344-49-4	iron hydroxide oxide
1333-86-4	Carbon black
136-52-7	cobalt bis(2-ethylhexanoate)
64742-88-7	Solvent naphtha (petroleum), medium aliph.
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
15956-58-8	Hexanoic acid,2-ethyl- manganese salt
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
107-98-2	1-methoxy-2-propanol
64742-48-9	Naphtha (petroleum), hydrotreated heavy
149-57-5	2-ethylhexanoic acid
147-14-8	Phthalocyanine Blue
79-09-4	propionic acid
95-63-6	1,2,4-trimethylbenzene
1330-20-7	xylene
108-67-8	mesitylene
7732-18-5	water, distilled, conductivity or of similar purity
· Canadian I	ngredient Disclosure list (limit 0.1%)
None of the	ingredients is listed.
· Canadian I	ngredient Disclosure list (limit 1%)
8052-41-3	Stoddard solvent

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

CHSOS

· Signal word Danger

· Hazard-determining components of labeling:

Stoddard solvent

octame thyl cyclotetrasilox ane

A mixture of: butan-2-one oxime and syn-O,O'-di(butan-2-one oxime)-diethoxysilane

· Hazard statements

Flammable liquid and vapour.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Do not breathe dust/fume/gas/mist/vapours/spray.

(Contd. on page 11)

Printing date 04/20/2017

Reviewed on 04/13/2017

Trade name: 13-8750 GREY AC ALKYD FLOOR HI GLOSS

(Contd. of page 10)

Wear protective gloves/protective clothing/eye protection/face protection.

Ground and bond container and receiving equipment.

Keep container tightly closed.

Use non-sparking tools.

Take actions to prevent static discharges.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace,

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: UCP PAINT
- · Date of preparation / last revision 04/20/2017 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative