SC6500 Battery Scrubber How To

Prepare for Use



SC6500 Battery Operator Use and Care for Disc and Cylindrical Models.

1

4

7

1

4



2

5

8

2

5

3

6

9

3

6

Prepare and inspect machine: disconnect battery charger, reconnect batteries. Close access cover. Verify hopper is empty. Inspect vacuum shut-off float and close recovery tank lid.



Perform a walk-around inspection.



Inspect and install brushes. Side brooms on Cylindrical models.



Brush installation - Disc models



Make sure squeegee is clean and ready for use. Connect the recovery hose to the squeegee inlet using hose clamp.



Adjust seat and steering wheel. Turn machine on, verify battery power, release brake, and drive to fill station.




Fill machine with water (add detergent as required). Fill solution tank with water only if using EcoFlex (refer to owner's manual).



Plan your cleaning route in advance then prepare to operate the machine.

SC6500 Battery Scrubber How To

Machine Operation & Maintenance Schedule



Press the solution switch. (hold for 5 seconds to pre-wet the floor).



Press the green Scrub On Switch to activate the scrub system. Set the chemical dilution ratio. Begin scrubbing.



Press the solution switch once to turn off solution flow while making sharp turns.



Release motion pedal to pause scrubbing.



To stop scrubbing press Scrub "OFF" button once.




Changing scrubbing power



Drive machine to designated disposal site to empty the solution and recovery tanks.



Wipe down the exterior of the machine.
Open recovery tank compartment. Prepare machine for storage and maintenance.



Prepare machine for storage and maintenance.



7

8