

Flat Surface Cleaners



◆ Economical DFSCP12E

- Full 12" cleaning path
- Can be connected directly to a gun, lance or telescoping wand
- Brass and stainless steel construction
- Durable polypropylene deck
- Includes a 1/4" plug for connecting to 1/4" quick disconnect



◆ Semi-Professional DFSCP12

- Full 12" cleaning path
- Can be connected directly to a gun, lance or telescoping wand
- Lightweight, anodized aluminum components
- Durable polypropylene deck
- Includes a 1/4" plug for connecting to 1/4" quick disconnect
- SKF stainless steel bearing for long lasting performance

FSC Model	DFSCP12E	DFSCP12
Maximum Flow	4 GPM	6 GPM
Operating Pressure	1000-3000 PSI	1500-3500 PSI
Shipping Weight	2.4lb	4lb
Dimensions-Retracted	12" x 5.3"	12.7" x 5.8"

Professional Flat Surface Cleaners



◆ DCFSCP18GZ, DCFSCP20GZ and DCFSCP24GZ

- Compensating gun feature
- Full 18", 20" and 24" cleaning paths
- Heavy-duty anodized aluminum components
- Rugged ABS cover
- Swivel has grease zerk fitting for bearing lubrication
- Two Stainless steel bearings for better performance
- Stainless steel inlet filter for water filtration
- 24" supplied with 3-nozzle rotating arm

FSC Model	DCFSCP18GZ	DCFSCP20GZ	DCFSCP24GZ
Maximum Flow		8 GPM	
Operating Pressure		1000-4000 PSI	
Caster kit		Not included	Included
Shipping Weight	17lb	21lb	23lb
Dimensions-Retracted	70" x 18.3" x 18.3"	70" x 21" x 21"	70" x 25" x 25"



DFSCGK Gun Cleaning Kit

- Works with all FSC shown on left
- Kit includes Gun, Lance and Ball Valve
- Use for quick spot cleaning
- **Gun Kit sold separately**

Flat Surface Cleaners

Above flat surface cleaners also available with SKF sealed swivels

Accessories for Flat Surface Cleaners



◆ 2103220 Swivel

- Swivel for the DCFSCP18GZ, 20GZ, 24GZ flat surface cleaners

◆ 2103226 Swivel

- Swivel for the DCFSCS22Z stainless steel flat surface cleaner

◆ 2100372 Swivel Major Repair

- Repair kit for both swivels



◆ 2100200 Caster kit

- Optional for DCFSCP18GZ and DCFSCP20GZ
- Stainless steel brackets
- Same casters used on DCFSCP24GZ and DCFSCS22Z



BiKleener – 2100473




BiKleener – 2100306

◆ Water Brooms

- Operating pressures: 2500 to 4500 PSI
- Quick connect to pressure washer wand
- 2 nozzle (2100473) and 3 nozzle (2100306) for a wide cleaning path
- Upright operation saves back strain and fatigue
- Consistent and even cleaning path - no zebra strips
- Cleaned area is easy to see and review
- Quick disconnects for easy storage
- 4 to 6 times faster saving energy and water


◆ Industrial Flat Surface Cleaner

DCFSCS22Z



- Compensating gun feature
- Full 22" cleaning path
- Heavy-duty anodized, aluminum components
- Rugged STAINLESS STEEL cover, handle & casters
- Three nozzle rotating arm
- Swivel has grease zerk fitting for bearing lubrication
- Stainless steel inlet filter for water filtration
- Operating Pressures: 1,000 to 4,000 PSI
- Max Flow: 8.0 GPM
- Dimensions: 70" x 23" x 23"
- Weight: 24.5 lbs.

◆ Rotary Arm assemblies



- 2530052: 2-nozzles rotary arm for the 18" flat surface cleaner
- 2530009: 2-nozzles rotary arm for the 20" flat surface cleaner



- 2103288: 3-nozzles SS rotary arm for the 24" flat surface cleaner
- 2103224: 3-nozzles SS rotary arm for the 22" flat surface cleaner



◆ D20015 Wand Support Belt

- Optional for the DLTG12, DCLTG18 and DCLTG24
- Reduces strain on back, shoulders, and arms of the operator



◆ Soap Shooter 100169-#3.5 100145-#4.0 100146-#4.5 100147-#5.0 100181-#6.0 101012-#7.0

- For use with lance or extension wand
- Adjustable chemical feature
- Chemical flow can be stopped
- 5000 PSI maximum
- Chemical does not go through pump
- Attaches to QC on lance or extension Wand
- Stainless Steel
- Includes: 30 foot hose filter and nozzle



Telescoping Wands



◆ Professional fiberglass series

DLTG12, DCLTG18 and DCLTG24

- Pole made of fiberglass and aluminum
- Use with hot or cold pressure washers
- Available in 12' (2-section), 18' (3-section) and 24' (4-section)
- Nozzle holder accepts standard quick couple spray nozzles
- 1/4" double-braid, 4000 PSI hose
- Exclusive General Pump Wand belt, D20015, available separately
- D20015 General Pump Wand belt not included

Wand Model	DLTG12	DCLTG18	DCLTG24
Maximum Flow		10.5 GPM	
Maximum Gun Pressure		4000 PSI	
Maximum Fluid Temperature		195°F	
Gun Type	Normal Gun	Compensating Gun	
Shipping Weight	9.2lb	11.6lb	14.2lb
Dimensions-Retracted	6.1" x 7' 1/2"	6.1" x 7' 5"	6.1" x 7' 8"



◆ Industrial Aluminum series

DCLTG18A and DCLTG24A4

- Extremely heavy-duty!
- Industrial, 5/16" double-braid, 4000 PSI hose
- All aluminum, lightweight pole
- Use with hot or cold pressure washers
- 18 foot 3-section telescoping poles
- 24 foot 4-section telescoping poles
- Nozzle holder accepts standard quick couple spray nozzles
- Compensating gun included
- Pin-lock adjustments
- Free! Exclusive D20015 General Pump Wand belt included in box!

Wand Model	DCLTG18A	DCLTG24A4
Maximum Flow		10.5 GPM
Maximum Gun Pressure		4000 PSI
Maximum Fluid Temperature		195°F
Gun Type	Compensating Gun	
Shipping Weight	13lb	16.5lb
Dimensions-Retracted	6.8" x 6' 5"	6.8" x 6' 8"



HAMMERHEAD FLAT SURFACE CLEANERS GIRAFFE TELESCOPING WANDS



GP Companies, Inc.
1174 Northland drive. Mendota Heights, MN 55120
Phone: 651.686.2199 Fax: 800.535.1745
www.generalpump.com email: sales@gpcompanies.com



General Pump
Is a member of
The Interpump Group