HOBART CENTERLINE DESCALING PROCEDURE

The dishwasher should be delimed on a regular basis as required. How often depends on the mineral content of the water. Deliming should be done when you can see clear signs of lime deposits (a white chalky substance) on the inside walls, on the wash and rinse arms or tank heater. Inspect the machine interior for lime deposits. When deliming is necessary, a deliming agent (such as Vestec 690 or Vestec 691) should be used for best results.

WARNING: CHEMICAL MIXING

Deliming solution must not come in contact with bleach or rinse solution containing bleach. Mixing may cause hazardous gas to form. This entire procedure must be followed step-by-step for safe and satisfactory results.

This machine is equipped with an automatic delime cycle reminder. It is recommended that deliming be done when the Delime button LED is flashing. Deliming can also be initiated at any other time if deemed necessary. Follow the steps below to delime the machine.

- 1. Machine must be on and at a ready state (Power/Drain button LED lit permanently).
- 2. Open the door, remove tank strainers. Rinse under running water.
- 3. Replace tank strainers.
- 4. Close door.
- 5. Press and hold the Delime button (minimum 3 seconds).
- 6. The upper display will show "SdL" to show that the delime cycle has started.
- 7. The machine will enter a drain and rinse phase. During this phase the delime button LED will be lit continuously.

NOTE: The deliming cycle is extensive and can take 30 minutes or more to complete.

- 8. When ready to add deliming agent, the upper display will show "Add". The delime button LED will flash.
- 9. Open the door.
- 10. Add 1-2 cups of Vestec 690 or Vestec 691, then close the door.
- 11. The deliming process will continue. The delime button LED will be lit continuously. The upper display will show "dL".
- 12. When the deliming phase completes, the machine will enter a drain and rinse phase. During this phase the delime button LED will be lit continuously.
- 13. After the deliming process is completed, the machine will drain and shut down.
- ▼ Toronto | Niagara Falls | Cambridge
- www.flexoproducts.com
- 1-800-263-2540

